





## T-Profile

### T-Profile PU85A sapphire blue smooth / ribbed (LGD) / Diamond (25 x 5 mm)



Order No.	Profile dimension mm	Cross section cm <sup>2</sup>	approx. Weight kg/100 m	Standard Roll		Recommended Min. pulley Ø		Fmax/belt (Standard)	
				m	ft	mm	inch	kg	lbs
FBSP85A25X5B	25 x 5	0,59	7,3	50	164	50	2,0	15,2	33,4
FBTK25X5LGA (ribbed)	25 x 5	0,59	7,3	50	164	50	2,0	15,2	33,4
FBTK25X5LW01 (Diamond)	25 x 5	0,59	7,3	50	164	50	2,0	15,2	33,4



Recommended pretension: 3...6 %, **Coeff. of friction μ:** Steel: approx. 0,60 | PE: approx. 0,35 | HDPE: approx. 0,30

approx. 88° Shore A

FDA/EC/USDA compliant

### Symbols

Antistatic profile with outstanding mechanical properties.	Profile with exceptional low-temperature flexibility down to -30°C.	Patented material formulation „PLUS“ for lower product elongation.	Very good UV resistance.	FDA/EC conformity for hydrolysis-resistant conveying profiles with rough and finely textured surfaces.	EC/FDA/USDA conformity for smooth profiles.	Metal and X-ray detectable profiles for maximum food safety.	Hydrolysis resistance (HY). Suitable for humid environments.	Microbe-resistant materials do not provide a breeding ground for micro-organisms